



Key Benefits and Features:

Western Digital PC SN740 NVMe™ SSD

PRODUCT BRIEF

NVMe™ SSD

Specifications

Capacity ²	256GB	512GB	1TB	2TB
Form Factor	Single side assembly, M key			
Security Protocol for Non-SED	TCG Pyrite 2.01 and ATA Security passthrough over NVMe			
Security Protocol for SED	TCG Opal 2.01			
Interface	PCIe Gen4 x4 NVMe v1.4b			
Performance ¹				
Sequential Read up to (MB/s)	4,000	5,000	5,150	5,150
Sequential Write up to (MB/s)	2,000	4,000	4,900	4,850
Random Read up to (IOPS)	270K	460K	740K	650K
Random Write up to (IOPS)	470K	800K	800K	800K
Endurance ³ (TBW)	200	300	400	500
Power				
Peak Power (10μs) (W)	4.7	5	6	6.3
Average Active Power ^{5,6} (mW)	50	50	65	65
Sleep (PS5) ⁵ (mW)	3.3	3.3	3.3	3.3
Supply Voltage (VDC/ ±5%)	3.3	3.3	3.3	3.3
Reliability				
MTTF ⁷	Up to 1.75M hours			
Environmental				
Operating Temperature ⁸	32°F to 185°F (0°C to 85°C)			
Non-Operating Temperature ⁹	-40°F to 185°F (-40°C to 85°C)			
Operating Vibration	5G _{RMS} ⁴ 10–2000Hz, 3 axes			
Non-Operating Vibration	4.9G _{RMS} ⁴ 7–800Hz, 3 axes			
Shock	1,500G @0.5 ms half sine, 3 pulses per face			
Certifications	Windows HLK, FCC, UL, TUV, KC, BSMI, VCCI, CE			
Limited Warranty ⁴	5 years			
Physical Dimensions				
Width	22mm ±0.15mm			
Length	M.2 2280: 80mm ±0.15mm, M.2 2230: 30mm ±0.15mm			
Thickness (max)	2.38mm (except M.2 2230 2TB: 2.48mm)			
Weight	M.2 2280: 5.4g ±0.5g, M.2 2230: 2.8g ±0.5g			
Ordering Information				
M.2 2280 Security Type: Non-SED	SDDPNQD-256G	SDDPNQD-512G	SDDPNQD-1T00	SDDPNQE-2T00
M.2 2280 Security Type: SED	SDDQNQD-256G	SDDQNQD-512G	SDDQNQD-1T00	SDDQNQE-2T00
M.2 2230 Security Type: Non-SED	SDDPTQD-256G	SDDPTQD-512G	SDDPTQD-1T00	SDDPTQE-2T00
M.2 2230 Security Type: SED	SDDQTQD-256G	SDDQTQD-512G	SDDQTQD-1T00	SDDQTQE-2T00

¹ 1 MB/s = 1 million bytes per second. Based on internal testing; performance may vary depending upon host device, usage conditions, drive capacity, and other factors. Performance is based on the CrystalDiskMark 8.0.1 benchmark using a 1000MB LBA range Asus ROG Maximus XIII Hero desktop with Intel i9-11900K @ 3.50GHz, 128GB 3200MHz DDR4. Microsoft Windows 10 Pro x64 2009 (19043.1023) using Microsoft StorNVMe driver, secondary drive. Performance may vary based on host device.

² 1 GB = one billion bytes and 1TB = one trillion bytes. Actual user capacity may be less depending on operating environment.

³ TBW (terabytes written) values calculated using JEDEC client workload (JESD219) and vary by product capacity.

⁴ 5-years or Max Endurance (TBW) limit, whichever occurs first. 5-year warranty in regions not recognizing "limited." See <http://support.wdc.com> for more details.

⁵ Average Power is measured using MobileMark™ 2018 on Dell Mobile precision workstation 3560 CTO, intel® Core™i7-1165G7, Windows 10 (version 19042) Bios version 1.5.1, Intel RST driver.

⁶ Power measurements at 25°C.

⁷ MTTF = Mean Time To Failure based on internal testing using Telcordia stress part testing. MTTF is based on a sample population and is estimated by statistical measurements and acceleration algorithms. MTTF does not predict an individual drive's reliability and does not constitute a warranty. (Telcordia SR-332, GB, 40°C).

⁸ Operational temperature is defined as temperature reported by the drive. Note that drive temperature readings are expected to be higher than ambient temperature when the SSD is placed inside a system.

⁹ Non-operating storage temperature represents ambient temperature and does not guarantee data retention beyond endurance and data retention specifications.



5601 Great Oaks Parkway
San Jose, CA 95119, USA
www.westerndigital.com

©2022 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the Western Digital design, and the Western Digital logo are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. The NVMe word mark is a trademark of NVM Express, Inc. PCIe is a registered trademark of PCI-SIG in the United States and/or other countries. All other marks are the property of their respective owners. References in this publication to Western Digital products, programs or services, do not imply that they will be made available in all countries. Product specifications provided are sample specifications and do not constitute a warranty. Actual specifications for unique part numbers may vary. Pictures shown may vary from actual products.